Replacement Of Cement With Rice Husk Ash In Concrete

LINGAMGUNTA SRAVANI

Mtech Student, Dept Of CIVIL
Pace Institute Of Technology And Sciences
Valluru, Ongole, Andhra Pradesh, India

P.RAVI KUMAR

Assistant Professor, Dept Of CIVIL
Pace Institute Of Technology And Sciences
Valluru, Ongole, Andhra Pradesh, India

Abstract: Rise in the need for conventional construction materials and the requirement for supplying a sustainable development in the development field has motivated they and developers to go for 'alternative materials' achievable to be used in construction. With this objective, using industrial waste material and farming byproducts are extremely constructive. These industrial wastes and farming by products for example Fly Ash, Grain Husk Ash, Silica Fume, and Slag could be replaced rather of cement due to their pozzolanic behavior, which otherwise requires large tract of lands for dumping. In our analysis, Grain Husk Ash has been utilized being an admixture to cement in concrete and it is qualities continues to be studied. An effort seemed to be completed to check out the strength and workability parameters of concrete. For normal concrete, mix design is performed according to Indian Standard (IS) method and using this as reference, mix design has been created for substitute of Grain Husk Ash.

Keywords: Rice Husk Ash (RHA); Industrial Waste; Concrete Mix;

I. INTRODUCTION

These days using concrete in infra- structural activity is rising with Cement being the most crucial but pricey element of concrete, effort to lessen the price by partial substitute of Cement with extra cementations materials has acquired momentum and it is even made like a government regulation. However, producing concrete isn't eco-friendly. Within this scenario, using conventional spend, such fly ash, Grain husk ash, Ground granulated blast furnace slag, silica fume, sugar cane biogases etc. like a substitute for Portland Cement in concrete presents one viable solution with multiple benefits for that sustainable growth and development of the concrete industry [1]. Presently, industrial waste for example Fly Ash (FA) and Grain Husk Ash (RHA) are used as extra Cement substitute materials. Therefore, an excellent potential exists to lessen the concrete industry's contributions to green house gases through decrease in Cement consumption.

Concrete: An artificially developed stone caused by hardening of a combination of a Cement, aggregates, and water without or with an appropriate admixture is often known as concrete. Concrete posses a higher compressive strength and it has an undesirable tensile strength. Additionally, it develops shrinkage stresses. It is understood to be the home of freshly mixed concrete or mortar which determines the convenience and homogeneity that it may be mixed, placed, consolidated and handle. Using plasticizers and super plasticizers greatly improve workability.

Fig.1.Rice husk Ash from paddy grain to grinded ash form

Segregation: A great concrete is a by which all of the ingredients for example Cement, aggregates and water are correctly distributed to create a homogeneous mixture. Segregation can be explained as “the separation of constituent materials of concrete”. Segregation could be of three types, the first is coarse aggregate out or settling lower in the rest, next the paste of matrix separates from coarse aggregate and lastly water separating from remaining material to be the material of cheapest specific gravity. Vibration of concrete is among the important ways of compaction. Segregation can be prevented by proper mix proportions, using air entraining agents and through proper handling, transporting, placing, compacting, finishing. Bleeding is a kind of segregation, where water arrives at first glance of concrete because it has cheapest specific gravity of all ingredients of concrete mix. Within the field, bleeding could be identified easily by the look of thin layer water on top of the top of fresh concrete.

Special Cements (OPC S): The Special Cements really are a special kind of Cements which can be used for the required needs. Among its OPC 53-S may be the special kind of Cements which can be used for construction of sleepers. OPC represents

Ordinary Portland Cement, 53 represent the compressive strength of Cement after 4 weeks curing, and S represents the special Cements [2]. It's a niche Cement manufactured according to specifications initially formulated through the Indian Railways vide their specs No.IRS T-40 for manufacturing concrete sleepers. However, there is an amendment (No.6) to IS 12269, IRS T-40 Cement after which, it was introduced underneath the ambit of BIS. It's now designated as 53-S Ordinary Portland cements and conforms to BIS specs IS: 12269-1987. 53-S OPC's minimal chloride content protects it against corrosion. High fineness enhances workability and early strength enables improved mass production cycle of Railway Sleepers. Aside from its primary usage within the output of concrete sleepers, it is also offer use within pretest concrete elements or high-rise structures where early strength is needed.

Aggregate: The aggregates possess a definite affect on the effectiveness of hardened concrete. Hence, the mixture employed for concrete ought to be durable, strong, chemically inert and well graded. The mixture occupies about 75% of the level of concrete plus they greatly influence the qualities of concrete. These gives body towards the concrete and lower the shrinkages aftereffect of Cement making the concrete durable.

Admixtures: Chemicals put into concrete to change a number of its mix qualities is known as being an admixture. It's surly a hard task to calculate the result of result enchantment in existence of admixture. Couple of admixtures affects several concrete properties and often we have to go in excess of one admixture for acquiring the preferred qualities in one mix. If such situation in excess of one admixture arises then your task of predicting the qualities become too hard [3]. Admixtures possessing pozzolona nature that contains Cementations anyway apart from Portland cement are utilized more generally. Based on market research of Portland Cement Association printed in 2000, around 60% of binding material in ready mix concrete contains other Cementations materials known as mineral admixtures also referred to as 'Supplementary Cementing Material'. These Mineral admixtures may come to make use of additionally towards the normal OPC amount or as an alternative with respect to the preferred qualities of concrete. Generally used when special performance is required in construction. With the addition of mineral admixtures strength is elevated, water demand, impermeability is reduced, low heat of hydration, greater age strength i.e., durability, charge of alkali-aggregate reactivity, retarding setting some time and reduces cost. Substitute of Cement by these mineral admixtures results in cost saving which is energy needed process. Ecological

damage and pollution is minimized by use of these byproducts.

Water: Water should be thought about being an important material for construction, where it's mainly combined with Cement to make mortar, concrete, etc. and for curing of Cement works. The appropriateness from the available water for that construction could be acquired in the data specified by IS 456 Clause 5.4.3. The pH value shouldn't be under 6.

Grain Husk Ash: India includes a large agribusiness sector that has achieved outstanding successes over decades. Grain paddy may be the primary food source for vast amounts of people. The paddy grain when generated to milling about 80% of weight is changed into grain and also the remaining 20% weight of paddy is switched into husk. In nearly all grain producing countries a lot of the husk created in the processing of grain is burnt or dumped as waste. This could mostly be prevented using the created husk as fuel within the boilers for paddy processing, which implies that husk functions as ideal fuel for electricity generation. The grain husk is abnormally full of ash when compared with other biomass fuels. Throughout the firing procedure for grain husk about 25% is changed into Grain husk ash and remaining is switched into organic volatile matter. The acquired grain husk ash is definitely an agro-waste material which has elevated levels of ash that contains 92 to 95% silica. It's highly porous and light-weight material rich in exterior area. Grain husk ash has lately been acknowledged as pozzolona. A pozzolona is really a siliceous/aluminous material which increases its strength and impermeability. There might be formation of void within the concrete mixes, if curing isn't done correctly. This cuts down on the strength and excellence of the concrete. RHA is finer than Cement getting really small particle size 25 microns, in order that it fills the interstices among the Cement. This reduces the amount of Cement.

Advantages: Grain husk ash (RHA) can be used high reactive pozzolanic material to improve the microstructure from the interfacial transition zone (ITZ) between your Cement paste and also the aggregate in high-performance concrete. The effective use of grain husk ash like a pozzolanic material in Cement and concrete provides several positive aspects.

Fig.2.Split tensile test

II. WORKING METHODOLOGY

The job methodology from the present thesis work contains assortment of recyclables, figuring out the physical qualities from the collected materials and confirming the exam leads to the conventional values. Further, figuring out the correct mix design by utilizing acquired physical qualities. With various trial mix designs preferred mix proportion is decided and additional work was ongoing using individuals proportions by growing the proportion of Grain Husk Ash utilized as an incomplete substitute of Cement. Hardened concrete tests like were conducted and outcome was determined. Because the mix would be a trial mix we are meant to cast couple of samples testing the prospective strength, once it's been clarified the tests where giving great results Mix variations like difference in binding material ratio could be selected [4]. Each variation is going to be labeled following a mix designation and also the samples is going to be casted for figuring out tests like Compressive Strength, Flexural Strength and Split tensile strength with standard specimen sizes and then on comparison between your results with rise in number of partial substitute of Grain Husk Ash. Cubes are casted of 100 x 100 x 100mm dimension to locate compressive strength, 150 x 300mm dimension cylinder to locate split tensile strength, 100 x 100 x 500mm prism to locate flexural strength. Altogether 10 mix designations happen to be created and every mix includes 15 cubes to become tested for several, 7, 14, 28 and 56days of curing duration similarly 3 cylinders and three prisms are casted to check for 4 weeks of curing duration.

Mix Design: The standard of concrete depends on this mixture style of the concrete. The mixes as much as M20 are nominal mix, i.e. M5, M10, M15, M20. Whereas this mixture above M20 was created mix. This mixture design relies in strength criteria and sturdiness criteria employed for moderate atmosphere. The ratios by weight of Cement, fine aggregate and coarse aggregate are acquired while using specifications succumbed IS: 10262-2009 receive below. These proportions are maintained strictly same through the casting process to acquire a uniform standard and workable

concrete mix. Normally Cubes were tested for compressive strength after 7 and 4 weeks curing. Within this thesis work age curing at 3, 7, 14, 28, 56days are conducted. The entire process of thinking about needed quantity of ingredients of concrete as well as calculating their relative amounts with the aim of manufacturing a concrete from the needed, strength, durability, and workability as economically as you possibly can, known as the concrete mix design. The proportioning of ingredients of concrete is controlled by the needed performance of concrete in 2 states, namely the plastic and also the hardened states. When the plastic concrete isn't workable, it can't be correctly placed and compacted. The compressive strength of hardened concrete that is generally regarded as a catalog of their other qualities, based upon many factors, e.g. w/c ratio quantity and quality of Cement, water, aggregate, exposure conditions, material qualities, mixing, placing, compaction and drenched condition.

III. TESTS ON CONCRETE

The technique adopted to get the design mix for M40 grade concrete is performed based on IS: 10262-2009. For fresh concrete the slump cone test continues to be conducted as well as for hardened concrete the tests like Compressive Strength for cubes of size 150mm x 150mm x 150mm, Flexural Strength for prisms of size 500mm x 100mm x 100mm and Split Tensile Strength for cylinders of size 150mm diameter by 300mm height continues to be conducted. There are lots of tests readily available for testing the caliber of concrete. In our work, machine mixing process is utilized. The person mix ingredients are considered using their proportions exactly and so the materials are put in machine. The types of materials are completely included their dry condition before water is added after which continuous revolution of three-5minutes of machine is performed after adding water. The prepared mix ended up being immediately employed for testing workability of fresh concrete mix. In situation of substitute Cement with Grain Husk Ash, the grain husk ash is completely combined with Cement in dry condition after which it was combined with aggregate and then on water is put into this mixture.

Casting of Examples: The surefire moulds are cleaned of airborne dust and applied with oil on every side before concrete is put to the moulds. The moulds are put on an amount platform. The mixed concrete is positioned within the oiled mold in 3 layers. After placing, each layer it's tampered 25 occasions utilizing a slandered tampered fishing rod [5]. The strokes permeated in to the underlying layer and also the bottom layer was ridded throughout its depth. After which filled concrete moulds are vibrated using machine vibrator. Excess concrete was removed with trowel and top surface

is completed level and smooth according to IS 516-1959.

Compaction of Concrete: Compaction of concrete is the procedure adopted for expelling the entrapped air in the concrete. While placing and mixing of concrete, air will probably get entrapped within the concrete. If air isn't removed fully, the concrete loses strength significantly. To have full compaction and maximum density Table vibrator can be used within this experiment.

Curing of Test Specimen: After casting, the molded examples are kept in laboratory in 70 degrees for twenty-four hrs. After these periods the examples were marked and taken off the moulds and immediately submerged in clean, freshwater curing tank for needed period according to IS 516-1969. The examples are cured for several, 7, 14, 28 and 56days in present experimental work.

Tests conducted on Concrete: Concrete exams are done on fresh and hardened concretes. The exam on fresh concrete provides the workability from the concrete mix which of hardened concrete provides the strength parameters like Compressive Strength, Flexural Strength and Split Tensile Strength which need to be determined on growing age concrete. And acquired results should match the standard specifications of code provision. Workability of fresh concrete is dependent upon following methods, Slump Test, Compacting Factor, and Vee- Bee Test

Compressive Strength: After 4 weeks of curing the sample cubes are tested for compressive strength under compressive testing machine. The exam samples are removed from curing tank a minimum of four to five hrs of testing. For just one trail a minimum of three examples should be tested. Concrete specimen cubes are utilized to determine compressive strength of concrete and were tested according to IS 516-1959.

IV. CONCLUSION

Early strength is slightly less in RHA Blended Cement Concrete compared to conventional concrete. A rise close to 23.one percent, 33.9% Compressive Strength for RHA blended Cement Concrete when substituted for 20% of OPC 53 Cement at 28 and 56 days chronological age of normal curing. A rise close to 17.two percent, 21.8% of compressive strength is noted for RHA blended Cement concrete when substituted for 20% of OPC 53-S Cements at age 28, 56 days normal curing. The split tensile, flexure strength outcomes of RHA blended Cement concretes when replaced as much as twenty percent is much more compared to conventional aggregate concrete at of 4 weeks of ordinary curing A rise of approximately 25 percent, 8.74% of Flexural and Split tensile strength for RHA blended Cement concrete when substituted

for 20% of OPC 53 Cement at 4 weeks chronological age of normal curing. Comparative study Grain Husk Ash concrete with assorted substitute percentages of RHA demonstrated that, a substitute degree of 20% RHA in concrete performs and shows better strength than other replacements. For M40 grade of concrete 20% substitute demonstrated better Compressive Strength than usual concrete as well as demonstrated better strength values in situation of Flexural and Split Tensile Strengths. Therefore, the optimum substitute degree of RHA is discovered to be 20% for M40 grade of concrete. Because the Grain Husk Ash is waste materials, it cuts down on the price of construction and reduces pollution in atmosphere.

Fig 3: Collection of Materials, Batching, and Weighing:Fig 4: Mixing and placing

Fig 5: Curing

V. REFERENCES

- [1] Deepa G Nair, K. Sivaraman, and Job Thomas (2013) “Mechanical Properties of Rice Husk Ash (RHA) – High strength Concrete”, American Journal of Engineering Research (AJER) e-ISSN: 2320-0847 p-ISSN: 2320-093, Volume-3 pp-14-19.
- [2] Makarand Suresh Kulkarni, Paresh GovindMirgal, Prajyot Prakash Bodhale, Tande S N (2014) “Effect of Rice Husk Ash on Properties of Concrete”, Journal of Civil Engineering and Environmental Technology, Print ISSN: 2349-8404; Online ISSN: 2349-879X; Volume 1, Number 1; August, 2014 pp. 26-2.
- [3] Sathish Kumar R (2012) “Experimental study on the properties of concrete made with alternate construction materials”, International Journal of Modern Engineering Research (IJMER) Vol. 2, Issue. 5, Sept.-Oct. 2012 pp-3006-3012.
- [4] Thiruchelvam S, “Efficiency of Rice Production and Issues relating to Cost of Production in the Districts of Anuradhapura and Polannaruwa”, Natn J, Sci.Foundation Sri Lanka 2005 33(4), October 2005, pp. 247-256
- [5] Uduweriya R B Y B, Subash C, Sulfy M M A and Sudhira De Silva (2010) “Investigation of Compressive Strength of concrete containing Rice Husk Ash”, International Conference on Sustainable Built Environment (ICSBE-2010) Kandy, 13-14 December 2010.

AUTHOR's PROFILE

Lingamgunta Sravani has received her B.Tech degree In Civil Engineering from Pace Institute Of Technology And Sciences, Valluru, Ongole in 2013 & she is now Pursuing the M.Tech degree at Pace Institute Of Technology And Sciences, Valluru, Ongole.

P.Ravi Kumar, received his M.Tech degree, currently He is working as an Assistant professor in Pace Institute Of Technology And Sciences, Valluru, Ongole.